QUALITY ALUMINUM BOAT LIFTS, INC. COMPONENT LIST

ELEVATOR LIFT

Quality Aluminum Boat Lifts, INC.

Component List: Elevator Lift

Thank you for your recent purchase of your Boat Lift, before Installation of your lift we encourage you to read all instructions entirely. Failure to do so could result in serious injury or death. We are happy to assist you with any Technical questions that you may have, please feel free to contact via email at the email address included.

The following lift Components included for the Elevator Lift 3K-16K. NOTE: If additional options have been purchase, these options will not be included on the components list.

MAJOR LIFT COMPONENTS:

MOTOR PLATE TO LIFT:

- (4) 1.5 x 1/2" HEX BOLTS
- (4) 1/2" WASHERS
- (4) 1/2" LOCK NUTS

MOTOR SPACERS:

(2) 2" PIPE 5 1/2" LONG WITH A 1/2" HOLE

BUNK BRACKETS & HARDWARE:

- (8) 2" X 2" ANGLE WITH 2 HOLES ON EACH SIDE OF THE ANGLE.
- (24) 3/8" HEX BOLTS
- (16) 3/8" WASHERS
- (8) LOC WASHERS
- (24) NUTS

GUIDE POST:

- (2) 10" X 12" FLAT PLATE WITH WELDED 2" BEARING TO HOLD WEIGHT PIPE
- (2) P.V.C. WITH (4) 3/8" HOLES
- (8) 3/8" LOC WASHER
- (4) ANGLED

PULLEYS AND AXLE BOLTS:

- (2) BOLTS
- (2) LOC NUTS
- (2) PULLEYS

BUNKS:

- (2) CARPETED BOARDS OR
- (2) ALUMINUM BUNKS
- (2) CRADLE ARMS
- (2) L SHAPED TRACKS
- (2) I BEAMS FROM 20' LONG TO 30'.

CABLES:

(2) CABLES

CROSS BRACING AND HARDWARE:

3K-10K (2) 12' LONG 3" X 3" X 3/8" ANGLE 13K/16K (6) PIECES 3" X 3" X 3/8" ANGLE

- (2) 1.5" X 3/8" HEX BOLT
- (2) 3/8" NUT
- (2) 3/8" LOC NUT

TOP CARRIERS:

- (2) COMPLETE WITH CABLE WINDERS
- (8) 1/2" X 1 3/4" HEX BOLTS
- (8) 1/2" LOC NUTS

DEADMAN:

- (2) ANGLED PIECES FROM 5" TO 7" DEPENDING ON THE SIZE OF THE LIFT.
- (6) 3/8" X 1.5" HEX BOLTS
- (6) LOC NUTS

CABLE CLAMPS:

(2) CABLE CLAMPS

COVERS:

- (2) COVERS
- (4) 1.5" HEX BOLTS
- (4) WASHERS
- (4) NUTS
- (2) SQUARE PLATES WITH OBLONG HOLES
- (4) WASHERS WITH WELDED PINS

DRIVE UNITS:

- (2) DRIVE PLATES
- (2) 10" PULLEYS
- (2) 2" PULLEYS
- (2) BELTS
- (2) SWITCHES WITH G.F.I.

OR

(1) REMOTE (OPTIONAL)

GUIDE POST AND PIPES:

- (2) P.V.C PIPES WITH CAPS
- (2) 4' WEIGHT PIPES 1.5" ROUND

DEADMAN BOLTS FOR 13K THRU 16KLB LIFTS ONLY:

- (2) 2.5" X 1/2" BOLTS
- (2) 1/2" WASHERS
- (2) LOC NUTS

KICKER BRACE:

(1) KICKER BRACES FOR SPANS OF OVER 13'

ZINCS:

- (1)ZINC MUSHROOM STYLE
- (1) 1/2" X 1" HEX BOLT
- (1) 1/2" LOC WASHER

REQUIRED TOOLS:

LEVEL HAMMER DRILL

3/8" METAL BIT

1/2" AUGER BIT TO DRILL PILINGS

RAZOR KNIFE

- (2) 3/4" WRENCH
- (2) 9/16" WRENCH
- (1) 7/16" WRENCH
- (2) 1 1/8" WRENCH
- (1) #2 PHILLIPS HEAD SCREW DRIVER

Any questions regarding the installation of your lift our technical experts are happy to assist you @ our email: qualityboatlift@gmail.com Attention: Technical Support. To quicken the process please add the pictures of the part or lift area you have questions about send to our staff also.

Thank you,

Quality Aluminum Boat Lifts, INC.